



- SPECIFICATION**
- VOLTAGE RATING: 125 VAC RMS.
  - CURRENT RATING: 1.5 AMP
  - CONTACT RESISTANCE: 40 mΩ MAX
  - INSULATION RESISTANCE: 500MΩ MIN.
  - WITHSTAND VOLTAGE: AC1000V RMS 50HZ or 60HZ MIN.
  - OPERATING TEMPERATURE: -40°C~+80°C

LED ELECTRICAL CHARACTERISTIC	
 9 Yellow LEFT LED	 11 Green RIGHT LED

Standard LED	Wavelength	Forward V (Min/Max)	Forward A	Type
Green	568nm	1.8V/2.8V	20mA	squareness
Yellow	585nm	1.8V/2.8V	20mA	squareness
Orange	610nm	1.8V/2.8V	20mA	squareness

g	LED-R	1	See Table 1	Tin PLATING
f	LED-L	1	See Table 1	Tin PLATING
e	SHELL	1	BRASS T=0.2mm	Ni PLATING
d	ME	1	BRASS T=0.35mm	Tin PLATING
c	TERMINAL	8	PHOSPHOR BRONZE T=0.35mm	Au/Tin PLATING
b	INSERT	1	PA9T UL94V-0	BLACK
a	HOUSING	1	PA9T UL94V-0	BLACK
NO.	PART NAME	QTY	MATERIAL	PLATING & COLOR
A0	RELEASED			Peng 02/08-17
REV	DESCRIPTION.	APPD.	Date	

# HUILYN

深圳惠興力电子有限公司  
SHEN ZHEN HUILY ELECTRONICS CO.,LTD.

FILE NO : HR6235S (Series)

TOLERANCE(公差):  
0.000 mm ± 0.075 mm  
0.00 mm ± 0.15 mm  
0.0 mm ± 0.25 mm

TITLE	PART NO.	DATE	SCALE	UNIT
RJ45, Shielded, Receptacle, Top Entry Surface Mount Type	HR6235S-1188N14B-21-2R	2017-08-02	1:1	mm
DRAWN BY	Peng	2017-08-02	REV.	inch
CHECKED BY	Zhu	2017-08-02	版本	A.0